

**Confidentiality Disclaimer:**

This document and the technology disclosed thereby is owned by Argent International, Inc. It contains confidential proprietary and/or trade secret information and must not be copied. The document and the information it contains must be used only by the recipient for the specific use for which it was requested. This document and all copies of it must be returned immediately upon the request to do so by Argent International, Inc

APPLICATION DATA SHEET

Note: If more information is needed please call for a technical data sheet.

PRODUCT: PUL 0612 High Performance Protective Film

PRODUCT DESCRIPTION: PUL 0612 is a clearcoated thermoplastic urethane protective film, specially designed to preserve the appearance and integrity of automotive finishes. The film is ideal for protecting high-wear areas from chipping, weathering and most other types of environmental damage.

MATERIAL:

Normal Thickness:	225 μ
Color:	Transparent
Surface:	High Gloss

Tested Properties	Required	Results
-------------------	----------	---------

Adhesion

- 30' at SLC	3,35 N/cm	14,1 N/cm
- 72h at SLC	5,25 N/cm	13,6 N/cm
- 7d at 80°C	7,00 N/cm	15,0 N/cm

Temperature Resistance

7d at 80°C	No Changes
- Long. Shrinkage	max. 0.5%
- Transversal Shrinkage	max. 0.5%
30 min at 120°C	No Changes
- Long. Shrinkage	max. 0.5%
- Transversal Shrinkage	max. 0.5%

Notice: All statements, information and data given herein are believed to be accurate and reliable. These values are intended as guides only and not as specification limits. This data is presented without guarantee, warranty or responsibility of any kind, expressed or implied. Statements or suggestions concerning possible use of our products are made without representation or warranty that any such use is free of patent infringement and are not recommendations to infringe any patent. The user should not assume that all safety measures are indicated or that other measures may or may not be required.