

**Confidentiality Disclaimer:**

This document and the technology disclosed thereby is owned by Argent International, Inc. It contains confidential proprietary and/or trade secret information and must not be copied. The document and the information it contains must be used only by the recipient for the specific use for which it was requested. This document and all copies of it must be returned immediately upon the request to do so by Argent International, Inc

APPLICATION DATA SHEET

Note: If more information is needed please call for a technical data sheet.

PRODUCT: ARV3200 - Flock Tape

PRODUCT DESCRIPTION: Flock tape excels in applications that require abrasion resistance and moderate sound dampening. Flock tape's dense nylon fibers form a cushion between mating components and resist crushing to effectively stop most squeak and rattle challenges. Our flock tape utilizes an OEM tested and approved, high-performance adhesive system, which provides excellent adhesion to most substrates. Its high-performance and low cost make it an excellent choice for a variety of BSR applications.

PROPERTIES:**VALUES:**

Construction:

100% Nylon, black

Abrasion Resistance, 500 Cycles, CS-10, 1.0kg load (Type I):

Wet (CS-10/500g): 1000 Cycles
Dry (CS-10/1000g): 1500 Cycles

Flammability:

FMVSS 302

	ABS	PP
Bond Peel Test - Original:	8.9 lbs/in	4.0 lbs/in
Bond Peel Test - 7d @ 79°C:	7.5 lbs/in	6.4 lbs/in

Notice: All statements, information and data given herein are believed to be accurate and reliable. These values are intended as guides only and not as specification limits. This data is presented without guarantee, warranty or responsibility of any kind, expressed or implied. Statements or suggestions concerning possible use of our products are made without representation or warranty that any such use is free of patent infringement and are not recommendations to infringe any patent. The user should not assume that all safety measures are indicated or that other measures may or may not be required.